



Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.
Issue date: 7/16/2025 Revision date: 7/16/2025 Version: 1.00

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance (UVCB)
Trade name : Total Resin Extract / Ethanol Extract
Chemical name : Hop, Humulus lupulus, ext.
EC-No. : 232-504-3
CAS-No. : 8060-28-4
EU REACH registration No. : 01-2120766018-52-xxxx

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Manufacturing of food

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier/Importer

Lupex GmbH
Eschenring 4
DE 84072 Au i. d. Hallertau
Deutschland
T +49 8752 / 86130
info@lupex.de

Manufacturer/Supplier

Hallertauer Hopfenveredelungsges. mbH (HHV)
Auhofstr. 18
84048 Mainburg
Germany
Email competent person
sds@kft.de

Manufacturer/Supplier

Hallertauer Hopfenveredelungsges. mbH (HHV)
Mainburger Str. 26
84072 Au i. d. Hallertau
Germany

Manufacturer/Supplier

Hopfenveredlung St. Johann GmbH
Mainburger Str. 15
93358 Train / St. Johann

1.4. Emergency telephone number

Emergency number : +49 8752 / 86 130 (Monday – Friday 07.00-17.00, Central European Time)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP)

: Warning

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.
Precautionary statements (CLP)	: P261 - Avoid breathing mist, vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective clothing, protective gloves, eye protection. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0), hop oil (8007-04-3), Ethanol (64-17-5)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0), hop oil (8007-04-3), Ethanol (64-17-5)

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0), hop oil (8007-04-3), Ethanol (64-17-5)

SECTION 3: Composition/information on ingredients

3.1. Substances

Substance type	: UVCB
Chemical name	: Hop, Humulus lupulus, ext.
CAS-No.	: 8060-28-4
EC-No.	: 232-504-3

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (Natural component)	CAS-No.: 468-28-0 EC-No.: 207-405-3 REACH-no: 01-2120766877-32-xxxx	15 – 30	Acute Tox. 4 (Oral), H302 (ATE=700 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
hop oil (Natural component)	CAS-No.: 8007-04-3 EC-No.: 640-023-9	3 – 12	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

Ethanol (substance with national workplace exposure limit(s))	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	≤ 0.3	Flam. Liq. 2, H225 Eye Irrit. 2, H319
--	---	-------	--

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Ethanol (substance with national workplace exposure limit(s))	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	(50 ≤ C < 100) Eye Irrit. 2; H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction. Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.
--	---

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapours, spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
- Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing mist, vapours, spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.
- Storage temperature : < 10 °C
- Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Ethanol (64-17-5)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Ethanol
AGW (OEL TWA)	380 mg/m ³
	200 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

8.1.4. DNEL and PNEC

Hop, Humulus lupulus, ext. (8060-28-4)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	21 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	10 mg/m ³
Long-term - systemic effects, dermal	3 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.058 mg/l
PNEC aqua (marine water)	0.0058 mg/l
PNEC aqua (intermittent, freshwater)	0.058 mg/l
PNEC aqua (intermittent, marine water)	0.0058 mg/l
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	21 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	10 mg/m ³
Long-term - systemic effects, dermal	3 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	1.87 µg/L
PNEC aqua (marine water)	0.187 µg/L
PNEC aqua (intermittent, freshwater)	1.87 µg/L
PNEC aqua (intermittent, marine water)	0.187 µg/L
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
Ethanol (64-17-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	267 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	380 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	114 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.96 mg/l
PNEC aqua (marine water)	0.79 mg/l
PNEC aqua (intermittent, freshwater)	2.75 mg/l

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

PNEC (Sediment)	
PNEC sediment (freshwater)	3.6 mg/kg dw
PNEC sediment (marine water)	2.9 mg/kg dw
PNEC (Soil)	
PNEC soil	0.63 mg/kg dw
PNEC (Oral)	
PNEC oral (secondary poisoning)	380 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	580 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Wear closed safety glasses. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. EN ISO 13688. EN 13034

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemically resistant protective gloves. Nitrile rubber. ISO 374-1. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Breathing apparatus with filter. Filter A (colour code: brown). EN 143. . Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: dark green.
Appearance	: Viscous.
Odour	: Not available
Odour threshold	: Not available

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 100 °C (DIN EN ISO 3679)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 6.2
Viscosity, kinematic	: 400 – 1000 mm²/s
Viscosity, dynamic	: 400 – 1000 mPa·s (45 °C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1 g/cm³ (20 °C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Hop, *Humulus lupulus*, ext. (8060-28-4)

LD50 oral	> 2000 mg/kg bodyweight
-----------	-------------------------

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
LD50 oral rat	700 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation. pH: 6.2
Serious eye damage/irritation	: Causes serious eye irritation. pH: 6.2
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Hop, Humulus lupulus, ext. (8060-28-4)	
Viscosity, kinematic	400 – 1000 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met).

Hop, Humulus lupulus, ext. (8060-28-4)	
EC50 - Crustacea [1]	> 5.8 mg/l (48 h; Daphnia magna; (OECD 202 method))
ErC50 algae	52.5 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))
Ethanol	
NOEC chronic algae	11.5 mg/l (72 h, Chlorella vulgaris, (OECD 201 method))

12.2. Persistence and degradability

Hop, Humulus lupulus, ext. (8060-28-4)	
Persistence and degradability	Readily biodegradable, failing 10-d window.
Biodegradation	26 % (28 d; (OECD 301D method))
3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Persistence and degradability	Readily biodegradable, failing 10-d window.
Biodegradation	26 % (28 d; (OECD 301D method))
Ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable.
Biodegradation	84 % (20 d; Literature data)

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

12.3. Bioaccumulative potential

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Partition coefficient n-octanol/water (Log Pow)	4 – 5.5 (40 °C; pH 7; (OECD 117 method))
Ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (24 °C; pH 7,4; (OECD 107 method))
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.7 – 2.9 (Quantitative structure-activity relationship (QSAR))
Ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	≈ 0.2 (Handbook and/or Scientific papers)
Ecology - soil	Small adsorption.

12.5. Results of PBT and vPvB assessment

Hop, Humulus lupulus, ext. (8060-28-4)	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0), hop oil (8007-04-3), Ethanol (64-17-5)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0), hop oil (8007-04-3), Ethanol (64-17-5)

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Take note of Directive 94/33/EC on the protection of young people at work.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	hop oil ; Ethanol
3(b)	Total Resin Extract / Ethanol Extract ; 3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one ; hop oil ; Ethanol
3(c)	hop oil

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Germany

Employment restrictions	: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
National Rules and Recommendations	: TRGS 400: Risk Assessment for Activities Involving Hazardous Substances. TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 510: Storage of hazardous substances in non-stationary containers. TRGS 520: Construction and operation of collection points and temporary storage for small amounts of hazardous waste. TRGS 900: Occupational Exposure Limits.
Water hazard class (WGK)	: WGK 1, Slightly hazardous to water (Classification according to AwSV; ID No. 6390).
Storage class (LGK, TRGS 510)	: LGK 10 - Combustible liquids.
Major Accidents Ordinance (12. BImSchV)	: Is not subject to the Major Accidents Ordinance (12. BImSchV)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Data sources : Information provided by the manufacturer. European Chemicals Agency, <http://echa.europa.eu/>. Supplier Safety Data Sheet.

Department issuing data specification sheet: : KFT Chemieservice GmbH
Im Leuschnerpark 3
D-64347 Griesheim

Phone: +49 69 305 34 700
Fax: +49 69 305 86 500
SDS Service: +49 69 305 34 740

Contact person : Dr. Stefanie Finsterbusch-Kettner

Other information : This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet. A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

Total Resin Extract / Ethanol Extract

Safety Data Sheet

This safety data sheet is for informational purposes only and does not fully comply with national legal requirements. The national distributor is responsible for a legally compliant safety data sheet.

H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

KFT SDS EU 00 - Version 24.2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.